

CEMBRIT

HEALTH AND SAFETY DATA SHEET

1.	Trade name	Cempanel
2.	Distributed by	Cembrit Ltd Studio 39, Thames Innovation Centre, 2 Veridion Way, Erith, DA18 4AL
3.	Product appearance	Light Grey smooth flat sheets
4.	Product composition	Cement, wood fibre chips and hydration additives.
5.	Physical & Chemical Properties	Std to HD 1250-1450kg/m ²
6.	Fire and Explosion Data	Class 'o' to BS 476 Part 6 & 7.
7.	Health Hazards, Precautions and First Aid	
	Exposure Limits	Total inhalable dust 10mgm 3-8 hour time weighted average
	Standard Inhalation:	Respirable dust 5mgm 3-8 hour time weighted average
	Health Hazards	Acute over exposure to dust may cause mild irritation and inflammation of the respiratory tract and organs.
	Precautions	Use approved respiratory protective equipment when airborne dust is present. Dust extraction equipment is advisable when cutting with power tools.
	First Aid	If irritation occurs, move to fresh air. If condition persists, seek medical advice.
	Eye Contact: Health Hazard Precautions	Mild discomfort caused by dust. Goggles should be worn when cutting or drilling. Flush with plenty of fresh water. Seek medical advice if discomfort persists.
	Skin Contact: Health Hazards	Prolonged contact may cause mild irritation. Precautions
	First Aid	Gloves should be worn when handling. Wash thoroughly with water.

HEALTH AND SAFETY DATA SHEET CONTINUED

Ingestion: Health Hazard	Ingestion of dust may cause mild discomfort. Avoid ingestion by taking normal hygiene precautions. Use dust masks where airborne dust is present.
First Aid	Give plenty of water.
Transport Precautions:	No special requirements.
Handling, processing & use precautions	Boards should be handled with care to avoid injury and placing unnecessary strain on handlers. Gloves should be worn.

For further advice, please
contact:

Cembrit Ltd.
Studio 39,
Thames Innovation Centre,
2 Veridion Way,
Erith,
DA18 4AL

Tel: 020 8320 1184
Fax: 020 8310 4803
e-mail: info@cembrit.co.uk

August 2017